

CCI MANUFACTURING IL CORPORATION

15550 Canal Bank Rd., P.O Box 339, Lemont, IL 60439 U.S.A. TEL +1-630-739-0606 FAX +1-630-739-1116

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations Revision Date: 9/23/2021 Version: 1.0

SECTION 1: IDENTIFICATION

1.1. Product Identifier

Product Form: Mixture

Product Name: GC DEF

Synonyms: GC Diesel Exhaust Fluid (GC DEF)

1.2. Intended Use of the Product

Use of the substance/mixture: Diesel Exhaust NOx Reducing Agent

1.3. Name, Address, and Telephone of the Responsible Party

Supplier	Name	CCi MANUFACTURING IL CORPORATION
	Address	15550 Canal Bank Road, Lemont, IL 60439
	Telephone	(630) 739-0606

1.4. Emergency Telephone Number

Emergency Number : 865-588-7488 ext. 2541 Opt 5, Pangean - CMD 770-355-5094

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the Substance or Mixture

Classification (GHS-US)

Not classified

2.2. Label Elements

GHS-US Labeling

No labeling applicable

2.3. Other Hazards

Exposure may aggravate those with pre-existing eye, skin, or respiratory conditions.

2.4. Unknown Acute Toxicity (GHS-US)

No data available

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Substance

Not applicable

3.2. Mixture

Name	Product Identifier	%	Classification (GHS-US)
Water	(CAS No) 7732-18-5	66.8 - 68.2	Not classified
Urea	(CAS No) 57-13-6	31.8 - 33.2	Not classified

Full text of H-phrases: see section 16

SECTION 4: FIRST AID MEASURES

4.1. Description of First Aid Measures

First-aid Measures General: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

First-aid Measures After Inhalation: When symptoms occur: go into open air and ventilate suspected area. Obtain medical attention if breathing difficulty persists.

First-aid Measures After Skin Contact: Remove contaminated clothing. Drench affected area with water for at least 15 minutes. Obtain medical attention if irritation develops or persists.

First-aid Measures After Eye Contact: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention if pain, blinking or redness persist.

First-aid Measures After Ingestion: Rinse mouth. Do NOT induce vomiting. Obtain medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/Injuries: Not expected to present a significant hazard under anticipated conditions of normal use.

Symptoms/Injuries After Inhalation: Prolonged exposure to liquid may cause a mild irritation.

Symptoms/Injuries After Skin Contact: May cause mild skin irritation.

Symptoms/Injuries After Eye Contact: Prolonged exposure to liquid may cause a mild irritation.

Symptoms/Injuries After Ingestion: Ingestion is likely to be harmful or have adverse effects.

4.3. Indication of Any Immediate Medical Attention and Special Treatment Needed

If exposed or concerned, get medical advice and attention.

Diesel Exhaust Fluid

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 5: FIRE-FIGHTING MEASURES

5.1. Extinguishing Media

Suitable Extinguishing Media: Use extinguishing media appropriate for surrounding fire.

Unsuitable Extinguishing Media: Do not use a heavy water stream. Use of heavy stream of water may spread fire.

5.2. Special Hazards Arising From the Substance or Mixture

Fire Hazard: Not considered flammable but may burn at high temperatures.

Explosion Hazard: Product is not explosive.

Reactivity: Hazardous reactions will not occur under normal conditions.

5.3. Advice for Firefighters

Precautionary Measures Fire: Exercise caution when fighting any chemical fire.

Firefighting Instructions: Use water spray or fog for cooling exposed containers.

Protection During Firefighting: Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal Precautions, Protective Equipment and Emergency Procedures

General Measures: Avoid breathing (vapor, mist, spray). Avoid prolonged contact with eyes, skin and clothing.

6.1.1. For Non-emergency Personnel

Protective Equipment: Use appropriate personal protection equipment (PPE).

Emergency Procedures: Evacuate unnecessary personnel.

6.1.2. For Emergency Responders

Protective Equipment: Equip cleanup crew with proper protection.

Emergency Procedures: Ventilate area.

6.2. Environmental Precautions

Prevent entry to sewers and public waters.

6.3. Methods and Material for Containment and Cleaning Up

For Containment: Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. **Methods for Cleaning Up:** Clear up spills immediately and dispose of waste safely. Absorb and/or contain spill with inert material, then place in suitable container.

6.4. Reference to Other Sections

See heading 8, Exposure Controls and Personal Protection.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for Safe Handling

Additional Hazards When Processed: When heated to decomposition, emits toxic fumes.

Precautions for Safe Handling: Avoid breathing vapors, mist, spray. Avoid prolonged contact with eyes, skin and clothing. **Hygiene Measures:** Handle in accordance with good industrial hygiene and safety procedures. Wash hands and other exposed areas with mild soap and water before eating, drinking, or smoking and again when leaving work.

7.2. Conditions for Safe Storage, Including Any Incompatibilities

Technical Measures: Comply with applicable regulations.

Storage Conditions: Store in a dry, cool and well-ventilated place. Keep container closed when not in use. Keep/Store away from direct sunlight, extremely high or low temperatures, incompatible materials.

Incompatible Products: Strong acids. Strong bases. Strong oxidizers. Hypochlorites.

7.3. Specific End Use(s)

Diesel Exhaust NOx Reducing Agent.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control Parameters

No additional information available

8.2. Exposure Controls

Appropriate Engineering Controls

: Ensure adequate ventilation, especially in confined areas. Ensure all national/local regulations are observed. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.

Personal Protective Equipment

: Gloves. Protective clothing. Protective goggles. Insufficient ventilation: wear respiratory protection.



Diesel Exhaust Fluid

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / N	Nonday, March 26, 2012 / Rules and Regulations
Materials for Protective Clothing	: Chemically resistant materials and fabrics.
Hand Protection	: Wear chemically resistant protective gloves.
Eye Protection	: Chemical goggles or safety glasses.
Respiratory Protection	: Use a NIOSH-approved respirator or self-contained breathing apparatus whenever
	exposure may exceed established Occupational Exposure Limits.
Other Information	: When using, do not eat, drink or smoke.
SECTION 9: PHYSICAL AND CHEN	AICAL PROPERTIES
9.1. Information on Basic Phys	ical and Chemical Properties
Physical State	: Liquid
Appearance	: Colorless, clear
Odor	: Slight Ammonia
Odor Threshold	: No data available
рН	: 9.8 - 10
Evaporation Rate	: No data available
Melting Point	: No data available
Freezing Point	: No data available
Boiling Point	: 104 °C (219.20 °F)
Flash Point	: Non-flammable
Auto-ignition Temperature	: No data available
Decomposition Temperature	: No data available
Flammability (solid, gas)	: No data available
Vapor Pressure	: No data available
Relative Vapor Density at 20 °C	: No data available
Relative Density	: No data available
Specific Gravity	: 1.087-1.093 @20°C (68°F)
Solubility	: Soluble in water.
Partition Coefficient: N-octanol/wate	r : No data available
Viscosity	: No data available

Viscosity

9.2. Other Information No additional information available

SECTION 10: STABILITY AND REACTIVITY

Reactivity: Hazardous reactions will not occur under normal conditions. 10.1.

10.2. Chemical Stability: Stable under recommended handling and storage conditions (see section 7).

10.3. Possibility of Hazardous Reactions: Hazardous polymerization will not occur.

10.4. Conditions to Avoid: Direct sunlight. Extremely high or low temperatures. Incompatible materials.

10.5. Incompatible Materials: Strong acids. Strong bases. Strong oxidizers. Hypochlorites.

10.6. Hazardous Decomposition Products: Nitrogen oxides. Irritating fumes.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. **Information On Toxicological Effects**

Acute Toxicity: Not classified

Water (7732-18-5)		
LD50 Oral Rat	> 90000 mg/kg	
Urea (57-13-6)		
LD50 Oral Rat	8471 mg/kg	
Skin Corrosion/Irritation: Not classified pH: 9.8 - 10		
Serious Eye Damage/Irritation: Not classified pH: 9.8 - 10		
Respiratory or Skin Sensitization: Not classified		

Germ Cell Mutagenicity: Not classified

Carcinogenicity: Not classified

Reproductive Toxicity: Not classified

Specific Target Organ Toxicity (Single Exposure): Not classified

Specific Target Organ Toxicity (Repeated Exposure): Not classified

Diesel Exhaust Fluid

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Aspiration Hazard: Not classified

Symptoms/Injuries After Inhalation: Prolonged exposure to liquid may cause a mild irritation.

Symptoms/Injuries After Skin Contact: May cause mild skin irritation.

Symptoms/Injuries After Eye Contact: Prolonged exposure to liquid may cause a mild irritation.

Symptoms/Injuries After Ingestion: Ingestion is likely to be harmful or have adverse effects.

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity	
Urea (57-13-6)	
LC50 Fish 1	16200 - 18300 mg/l (Exposure time: 96 h - Species: Poecilia reticulata)
EC50 Daphnia 1	3910 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])
12.2. Persistence and Degradability	
Diesel Exhaust Fluid	
Persistence and Degradability	Not established.
12.3. Bioaccumulative Potential	
Diesel Exhaust Fluid	
Bioaccumulative Potential	Not established.
Urea (57-13-6)	
BCF fish 1	< 10
Log Pow	-1.59 (at 25 °C)
12.4. Mobility in Soil No additional inf	formation available
12.5. Other Adverse Effects	
Other Information	: Avoid release to the environment.
SECTION 13: DISPOSAL CONSIDERAT	IONS
13.1. Waste treatment methods	
Waste Disposal Recommendations: Dispos	se of waste material in accordance with all local, regional, national, and international
regulations.	
SECTION 14: TRANSPORT INFORMAT	TION
14.1. In Accordance with DOT Not re	egulated for transport
14.2. In Accordance with IMDG Not re	egulated for transport
14.3. In Accordance with IATA Not re	egulated for transport
SECTION 15: REGULATORY INFORM	ATION
15.1 US Federal Regulations	
Water (7732-18-5)	
Listed on the United States TSCA (Toxic Sub	istances Control Act) inventory
Urea (57-13-6)	
Listed on the United States TSCA (Toxic Sub	stances Control Act) inventory
15.2 US State Regulations	
Urea (57-13-6)	
U.S Minnesota - Hazardous Substance Lis	t
U.S Texas - Effects Screening Levels - Long	g Term
U.S Texas - Effects Screening Levels - Shor	rt Term
SECTION 16: OTHER INFORMATION,	INCLUDING DATE OF PREPARATION OR LAST REVISION
Revision Date	: 09/23/2014
Other Information	: This document has been prepared in accordance with the SDS

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

1910.1200.

requirements of the OSHA Hazard Communication Standard 29 CFR

SDS US (GHS HazCom)