



Genuine Chemistry

From the Manufacturer of OEM Fluids



Universal Blue Super Extended Life Prediluted Antifreeze/ Coolant

TECHNICAL DATA SHEET

Ver. 23-01

DESCRIPTION and APPLICATIONS

GC UNIVERSAL BLUE SUPER EXTENDED LIFE PREDILUTED ANTIFREEZE/COOLANT is a Ready-To Use Hybrid Phosphate-Enhanced Organic Acid Technology (POAT) ethylene glycol-based coolant with an inhibitor package that uses organic acid inhibitors (non-2EH) with ultra-low concentration of fully stabilized phosphate and without any nitrites, amines, borates or silicates. It is specifically designed to be used in traditional internal combustion engines in light or medium-duty applications to provide long-lasting, complete protection for all cooling system components as well as modern models equipped with indirect cooling battery systems based on electric (EV), hybrid (HEV) and plug-in-hybrid (PHEV) designs.

It is recommended for use in any vehicle using universal coolant formulation with on-road and off-road diesel, gasoline and natural gas engines applications as well as industrial, farming, mining, construction, and military equipment.

PERFORMANCE FEATURES and BENEFITS

- **Extended life organic acid (non-2EH acid) hybrid technology**
Works in all engine applications. When used as directed, the product will provide long-lasting protection for modern engines.
- **Free from 2EH acid, amines, borates, nitrites, and silicates**
This formulation provides excellent heat transfer capabilities for high-temperature applications and a stable/complete inhibitor package free of amines, silicates, borates, nitrites, and 2EH acid. It is therefore the recommended choice for engine and vehicle OEMs around the globe.
- **Outstanding corrosion protection**
This product provides excellent corrosion protection as confirmed through numerous OEM tests and demonstrated in evaluations under ASTM D3306 and D4985 specifications. It eliminates the need for SCA and chemically-charged filters.
- **Compatibility**
This non-abrasive product is fully compatible with other similarly formulated hybrid and OAT engine coolants and may improve water pump seal life. This formula can be mixed with other coolants (which should be kept below 25% to maintain corrosion protection properties) and provides exceptional long-term elastomer compatibility.
- **Long shelf life**
When stored in the original packaging away from moisture and direct sunlight, this product should be suitable for use up to 3~5 years after the manufacturing date. Shake well before use.

GC Universal Blue Super Extended Life Prediluted Antifreeze/Coolant



SPECIFICATIONS and APPROVALS

Meets or exceeds these requirements:

ASTM D4985, ASTM D3306, JIS K2234, TMC RP 329, Ford WSS-M97B57-A1, Ford WSS-M97B57-A2, BS 6580, GB 29743, GM 1825M, 1899M, Ford ESE-M97B44A, Chrysler MS 7170, AS/NZS 2108

TYPICAL PHYSICAL and CHEMICAL CHARACTERISTICS

PROPERTIES	ASTM TEST METHOD	TYPICAL VALUES FOR	
		ASTM D3306 Limits	50/50 Prediluted
Appearance/Color	Visual	Distinctive	Blue
pH, 50 vol%	D1287	7.5- 11.0	7.6
Conductivity, us/cm	APHA 2510	Report	<5000
Freezing point, 50 vol%	D1177, D6660, D3321	-34°F (-36.4°C)	-34°F (-37°C)
Ash content, mass %	D1119	2.5 max	<2.5
Chloride, ppm	D3634	25 max	<25
Total water, mass %	D1123	Report	< 50

These characteristics are typical of current production.

FREEZE/BOIL PROTECTION CHART	Coolant/Water Ratio	PROTECTS FROM (typical values)	
		Freezing Down to	Boiling Up to*
	50/50	-34°F	265°F

*- Using a 15 PSI Pressure Cap in Good Condition; ⁱ - Proper maintenance requires a complete cooling system flush, fill and subsequent topping off as needed with the same product at 50/50 dilution or mixture of concentrate with high-quality water to achieve 50/50 coolant-water ratio.

SHIPPING INFORMATION

Part #	Unit	Size	Dimensions (")	Unit weight (lbs.)	Units per Pallet	Pallets per Truck	Pallet weight (lbs.)
GC-C2U01-U-01-01	Case	6/1 gal	15.8L X 12.8W X 12.25H	60	36	20	2,210

ADDITIONAL INFORMATION

For proper freezing and boiling protection, use a traditional refractometer or hydrometer with ethylene glycol scale. Product should be kept away from children and animals to prevent potential exposure. A bittering agent is added to help reduce the potential for accidental ingestion of this product. For more information see Safety Data Sheet for appropriate products. Always dispose used coolant in accordance with local, state and federal guidelines.