



Genuine Chemistry
From the Manufacturer of OEM Fluids



GC®

DOT 3/4 Brake Fluid

PRODUCT DESCRIPTION

GC® DOT 3/4 Brake Fluid is a borate free, high quality hydraulic brake fluid based on polyglycols and polyglycol esters. Corrosion protection is provided by a State-of-the-Art inhibitor package.

PRODUCT BENEFITS

GC® DOT 3/4 Brake Fluid offers the following benefits:

- Meets All Federal Motor Vehicle Safety Standard (FMVSS), and applicable ISO, SAE Specifications
- Environmentally Friendly (contains no borates)
- Excellent Lubrication and Viscosity Properties
- Mixes with Conventional Brake Fluid
- Excellent Temperature Resistance to Oxidation
- Prolonged Compatibility with Elastomers
- Excellent Corrosion Protection for Different Metal Components
- Low Viscosity to meet Class 6 minus 40°C viscosity parameters for Advanced Braking System

APPLICATIONS

GC® DOT 3/4 Brake Fluid is recommended for disc brake, ESP and ABS braking systems with elevated demands due to higher operating temperatures. Additionally, GC DOT 3/4 Brake Fluid is well suited for severe driving conditions such as towing, extreme cold and high humidity. All vehicles, including internal combustion engine vehicles, as well as battery electric, hybrid, BEV plug-in vehicles with braking regenerations systems are protected by GC DOT 3/4 Brake Fluid.

SPECIFICATIONS and APPROVALS

Meets or exceeds these requirements:

- FMVSS #116
- SAE J1703

TECHNICAL DATA SHEET

Ver. 22-01

GC® DOT 3/4 Brake Fluid



PROPERTIES

GC® DOT 3/4 Brake Fluid retains excellent performance characteristics over long periods including exposure to high humidity as well as high temperature, and low temperature climates. GC® DOT 3/4 Brake Fluid is a versatile brake fluid, meeting multitude of performance based on environmental friendliness and superiority in boiling point and viscosity.

PROPERTIES	FMVSS Specification		GC Brake Fluid EVO
	DOT 3	DOT 4	DOT 3/4
Dry Boiling Point, °F (°C), (ERBT)	401°F (205°C)	446°F (230°C)	509°F (265°C)
Wet Boiling Point, °F (°C), (ERBP)	284°F (140°C)	311°F (155°C)	311°F (155°C)
Viscosity (mm ² /s) at -40°C	≤1500mm ² /s	≤1800mm ² /s	685mm ² /s
Viscosity (mm ² /s) at 100°C	≥1.5mm ² /s	≥1.5mm ² /s	1.80mm ² /s

Always use vehicle manufacturers recommendation for type and class of brake fluid for your vehicle. Store brake fluid in a dry place with the cap securely tightened. Before opening the brake fluid reservoir, clean the surrounding area to prevent dirt or grease from contaminating the brake fluid. Do not open any part of brake fluid system in an area of airborne dust or dirt. Every time you open the hood, check the fluid level, and fill the reservoir to the level recommended by the vehicle manufacturer.

Due to continual product research and development, the information contained herein is subject to change without notice.

SHIPPING INFORMATION

Part #	Unit	Size	Dimensions (")	Unit weight (lbs.)	Units per Pallet	Pallets per Truck	Pallet weight (lbs.)
GC-B5U00-U-12-01	Case	24/12 Ounce	16.11L x 11.05 W x 6.04 H	23.7	54	24	1,279.8

Genuine Chemistry